

RMP

COMPRESSORS



OPENWELL SUBMERSIBLE PUMP

RMP COMPRESSORS

MODEL	KW	HP	PIPE SIZE IN mm	Discharge in LPH	TOTAL HEAD IN METERS								
					10	15	20	25	30	40	50	60	
RHOP 0.5	0.37	0.5	32 x 25		9600	7200	3800	600					
RHOP E 1	0.75	1	32 x 25		10200	8300	6500	3500					
RHOP 1	1.5	2	50 x 25		10500	10100	9800	9500	8900	7400	3200		
RHOP DLX 1	0.75	1	25		11350	10350	9050	7050	3500				

- Stainless steel motor body, Shaft & Fasteners.
- High grade castings with rust preventive coating.
- High quality double lip oil seal.
- High quality LTB 4 earing bushes and thrust pad.
- Dynamically balanced impeller & rotor shaft.
- High quality polywrap E.C. grade copper wire.
- Powder coated C.I. components.



OUR UNIQUE DESIGN FOR OPENWELL SUBMERSIBLE PUMP



- Unique pump design eliminating use of bend pipe.
- design ensures water level is always above the Motor thus ensuring enhanced pump life.
- A better design for improved performance and Enhanced pump life.
- The upright unique design eliminates pump Jamming due to small pebbles or slurry.

Dealer / Sales specialist



RMP COMPRESSORS

Appanaicken palayam road,
Thudiyalur
Coimbatore - 641 034
Tamilnadu, india .